

os165 Powerful Dehumidifier




165 ltrs/day
extraction capacity



Recommended up to 16500 cu.ft.
indicative coverage area



Stainless Steel Body
SS304 body – anti corrosive and easy cleaning



Corrosive Resistant Condenser Evaporator
long life and higher efficiency



Dual Drainage Option
water pump + water tank



Optimum Dehumidifying Performance
high air flow at 1800 m³/hr



Easy Mobility
with castors



os165 dehumidifier

Specifications	Body Material	SS 304
	Extraction (l/24hr) (30°C, 80% RH)	165 litres/day
	Coverage Area	16500 cu. ft.
	Dimensions	625*435*1600 mm
	Power consumption, Power supply 220V-240V/50Hz	2120 watts
	Electric Current(A)	9.6A
	Air Flow	1800 m³/hr
	Refrigerant	R-410a
	Compressor	Panasonic (Rotary Type)
	Noise Level (approx.)	≤ 63 db (A)
	High Pressure	26 kgf/m2
	Low Pressure	8 kgf/m2
	Tank Capacity (SS tank)	6.5 litres
	Water Pump	Max : 4 - 4.5 meters height
	Weight	110 kg
Running Temperature	5°C – 35°C	



Industries



Healthcare



Pharma



R & D



Hotel



Warehousing



Printing



Food



Museum &
Art Galleries



Defense